AMENDMENTS TO THE CLAIMS

1. - 9. (Cancelled)

10. (Currently Amended) An electric double layer capacitor, comprising an electrode and an electrolyte for the electric double layer capacitor, wherein an electrode layer comprising the following copolymer (A) and an active material for the electrode is bonded to a current collector:

a copolymer (A)

comprising:

monomer units derived from at least one compound (a) represented by the following general formula (1):

 $CH_2=CR^1COOR^2$ (1)

wherein R¹ represents a hydrogen atom or a methyl group, and R² represents an alkyl group or a cycloalkyl group, the glass transition temperature obtained by homopolymerizing the compound (a) being less than 0°C, and

monomer units derived from at least one compound (b) selected from acrylic acid alkyl esters, methacrylic acid alkyl esters, aromatic vinyl compounds, and α,β -unsaturated nitrile compounds, the glass transition temperature obtained by homopolymerizing

Application No. 10/567,119 Docket No.: 4670-0118PUS1 Amendment dated June 29, 2009

Reply to Office Action of December 29, 2008

the compound (b) being 0°C or higher;

wherein the total content of the monomer units derived from the compound (a) and those

derived from the compound (b) is 90% or more by weight per 100% by weight of the whole

copolymer (A), and

the glass transition temperature of the copolymer (A) is 10°C or lower,

wherein the electrolyte includes tetraethylammonium tetrafluoroborate,

triethylmonomethylammonium tetrafluoroborate, or tetraethylammonium hexafluorophosphate.

11. (Previously Presented) The electric double layer capacitor according to claim 10.

wherein the copolymer (A) further comprises monomer units derived from an ethylenically

unsaturated carboxylic acid (c) in an amount of 0.1 to 10% by weight per 100% by weight of the

whole copolymer (A).

12. (Previously Presented) The electric double layer capacitor according to claim 10,

wherein R² in the general formula (1) is an alkyl group having 4 to 12 carbon atoms.

13. (Previously Presented) The electric double layer capacitor according to claim 10,

wherein the electrode layer further comprises a thickener in an amount of 0.5 to 5% by weight per

100% by weight of the active material for the electrode.

14. (Previously Presented) The electric double layer capacitor according to claim 13,

3

wherein the thickener is a cellulosic polymer.

MSW/LCL/lir